



# SAFETY DATA SHEET

Version #: 02  
Issue date: 08-February-2023  
Revision date: 21-February-2023  
Supersedes date: 08-February-2023

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Name of the substance** European Grade Gasolines - All Grades (Refer to Synonyms for Product Name)  
**Identification number** 649-378-00-4 (Index number)  
**Registration number** 01-2119471335-39-0088  
**Synonyms** En-228 European Premium Gasoline \* Premium Gasoline - 60KPA DVPE 10PPM SUL \* Premium Gasoline - 70KPA DVPE 10PPM SUL \* Premium Gasoline - 80KPA DVPE 10PPM SUL \* Premium Gasoline - 90KPA DVPE 10PPM SUL \* Premium Gasoline - 95KPA DVPE 10PPM SUL \* Premium Gasoline - 100KPA DVPE 10PPM SUL \* En-228 European Super Gasoline \* Super Gasoline - 60KPA DVPE 10PPM SUL \* Super Gasoline - 70KPA DVPE 10PPM SUL \* Super Gasoline - 80KPA DVPE 10PPM SUL \* Super Gasoline - 90KPA DVPE 10PPM SUL \* Super Gasoline - 95KPA DVPE 10PPM SUL \* Super Gasoline - 100KPA DVPE 10PPM SUL \* Sub Octane Prem. Gasoline Blendstock  
**SDS number** 2000

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Use as a fuel.  
A complete list of registered uses for this product can be found in the table of content of the exposure scenario for communication, available as an annex to the eSDS.  
**Uses advised against** All other uses.

### 1.3. Details of the supplier of the safety data sheet

#### Supplier

**Company name** Valero Energy Ltd  
1st Floor, Block B  
**Address** D22 X0Y3, Quarryvale  
Ireland  
**Telephone** 01/210 345 4593 (General information; US)  
**e-mail** CorpHSE@valero.com  
**Contact person** Industrial Hygienist

**1.4. Emergency telephone number** 0044/(0)18 65 407333

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

The substance has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

#### Classification according to Regulation (EC) No 1272/2008 as amended

##### Physical hazards

Flammable liquids Category 1 H224 - Extremely flammable liquid and vapour.

##### Health hazards

Skin corrosion/irritation Category 2 H315 - Causes skin irritation.  
Germ cell mutagenicity Category 1B H340 - May cause genetic defects.  
Carcinogenicity Category 1B H350 - May cause cancer.  
Reproductive toxicity Category 2 H361 - Suspected of damaging fertility or the unborn child.  
Specific target organ toxicity - single exposure Category 3 narcotic effects H336 - May cause drowsiness or dizziness.  
Aspiration hazard Category 1 H304 - May be fatal if swallowed and enters airways.

##### Environmental hazards

Hazardous to the aquatic environment, long-term aquatic hazard Category 2 H411 - Toxic to aquatic life with long lasting effects.

## 2.2. Label elements

### Label according to Regulation (EC) No. 1272/2008 as amended

Contains: Gasoline

#### Hazard pictograms



Signal word: Danger

#### Hazard statements

H224	Extremely flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
H361	Suspected of damaging fertility or the unborn child.
H411	Toxic to aquatic life with long lasting effects.

#### Precautionary statements

##### Prevention

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

##### Response

P301 + P310	IF SWALLOWED: Immediately call a POISON CENTRE/doctor.
P331	Do NOT induce vomiting.

##### Storage

Not assigned.

##### Disposal

Not assigned.

#### Supplemental information on the label

None.

## 2.3. Other hazards

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Hydrogen sulphide (H<sub>2</sub>S) can accumulate in the headspace of storage tanks and reach potentially hazardous concentrations. This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The mixture does not contain any substances included in the list established in accordance with REACH Article 59(1) for having endocrine disrupting properties at a concentration equal to or greater than 0.1% by weight. The mixture does not contain any substances having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0.1% by weight.

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

#### General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Gasoline	100	86290-81-5 289-220-8	01-2119471335-39-0088	649-378-00-4	
<b>Classification:</b> Flam. Liq. 1;H224, Skin Irrit. 2;H315, Muta. 1B;H340, Carc. 1B;H350, Repr. 2;H361, STOT SE 3;H336, Asp. Tox. 1;H304, Aquatic Chronic 2;H411					
P					

#### Composition comments

This product is registered under the REACH Regulation 1907/2006 as a UVCB. All concentrations are in percent by weight unless ingredient is a gas.

Hydrogen sulphide (H<sub>2</sub>S) can accumulate in the headspace of storage tanks and reach potentially hazardous concentrations. The full text for all H-statements is displayed in section 16.

Note P: The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 (Table 3.1) shall apply. This note applies only to certain complex oil-derived substances in Part 3.

## SECTION 4: First aid measures

#### General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

#### 4.1. Description of first aid measures

<b>Inhalation</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison centre or doctor/physician if you feel unwell.
<b>Skin contact</b>	Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Call a physician or poison control centre immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

**4.2. Most important symptoms and effects, both acute and delayed** Aspiration may cause pulmonary oedema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Direct contact with eyes may cause temporary irritation. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

**4.3. Indication of any immediate medical attention and special treatment needed** Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

### SECTION 5: Firefighting measures

**General fire hazards** Extremely flammable liquid and vapour.

#### 5.1. Extinguishing media

**Suitable extinguishing media** Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO<sub>2</sub>).

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

**5.2. Special hazards arising from the substance or mixture** Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

#### 5.3. Advice for firefighters

**Special protective equipment for firefighters** Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

**Special fire fighting procedures** In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

**Specific methods** Use standard firefighting procedures and consider the hazards of other involved materials.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** Wear appropriate personal protective equipment.

**For emergency responders** Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Use personal protection recommended in Section 8 of the SDS.

**6.2. Environmental precautions** Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

**6.3. Methods and material for containment and cleaning up** Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. The product is immiscible with water and will spread on the water surface. Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labelled containers.

**6.4. Reference to other sections** For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Before entering storage tanks and commencing any operation in a confined area check the atmosphere for oxygen content and flammability. (Subject to applicability) If sulphur compounds are suspected to be present in the product, check the atmosphere for H<sub>2</sub>S content. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

### 7.2. Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see section 10 of the SDS).

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ANNEX 1, PART 1 Categories of dangerous substances

Hazard categories in accordance with Regulation (EC) No 1272/2008

- P5a FLAMMABLE LIQUIDS (Lower-tier requirements = 10 tonnes; Upper-tier requirements = 50 tonnes)

- E2 Hazardous to the Aquatic Environment Chronic (Lower-tier requirements = 200 tonnes; Upper-tier requirements = 500 tonnes)

### 7.3. Specific end use(s)

Observe industrial sector guidance on best practices. For detailed information, see section 1.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### Ireland. Occupational Exposure Limits

Material	Type	Value
Gasoline (CAS 86290-81-5)	STEL	500 ppm
	TWA	300 ppm
Impurities	Type	Value
Benzene (CAS 71-43-2)	TWA	3.25 mg/m <sup>3</sup>
		1 ppm

##### EU. OELs, Directive 2004/37/EC on carcinogen and mutagens from Annex III, Part A

Impurities	Type	Value
Benzene (CAS 71-43-2)	TWA	3.25 mg/m <sup>3</sup>
		1 ppm

#### Biological limit values

No biological exposure limits noted for the ingredient(s).

#### Recommended monitoring procedures

Follow standard monitoring procedures.

#### Derived no effect levels (DNELs)

##### General population

Product	Value	Assessment factor	Notes
European Grade Gasolines - All Grades (Refer to Synonyms for Product Name) (CAS 86290-81-5)			
Long-term, Local, Inhalation	178.57 mg/m <sup>3</sup>	10	
Short-term, Local, Inhalation	640 mg/m <sup>3</sup>	15	
Short-term, Systemic, Inhalation	1152 mg/m <sup>3</sup>	15	

##### Workers

Product	Value	Assessment factor	Notes
European Grade Gasolines - All Grades (Refer to Synonyms for Product Name) (CAS 86290-81-5)			
Long-term, Local, Inhalation	837.5 mg/m <sup>3</sup>	6	
Short-term, Local, Inhalation	1066.67 mg/m <sup>3</sup>	9	
Short-term, Systemic, Inhalation	1286.4 mg/m <sup>3</sup>	9	

#### Predicted no effect concentrations (PNECs)

Not available.

## Exposure guidelines

### Ireland Exposure Limit Values: Skin designation

Benzene (CAS 71-43-2)

Can be absorbed through the skin.

## 8.2. Exposure controls

### Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

### Individual protection measures, such as personal protective equipment

#### General information

Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

#### Eye/face protection

Wear safety glasses with side shields (or goggles). Eye protection should meet standard EN 166.

#### Skin protection

##### - Hand protection

Wear suitable gloves tested to EN374. In full contact: Glove material: Nitrile rubber. Layer thickness: 0.225 mm. Breakthrough time: >480 min. Splash contact: Glove material: Neoprene; Layer thickness: 0.75 mm; Breakthrough time: 10-30 min.

##### - Other

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

#### Respiratory protection

In case of inadequate ventilation or risk of inhalation of oil mist, suitable respiratory equipment with combination filter (type A2/P2) can be used.

#### Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

### Hygiene measures

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Form	Liquid.
Colour	Colourless.
Odour	Not determined.
Melting point/freezing point	< -60 °C (< -76 °F)
Boiling point or initial boiling point and boiling range	> 30 - < 260 °C (> 86 - < 500 °F)
Flammability	Extremely flammable liquid and vapour.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	Not determined.
Explosive limit – upper (%)	Not determined.
Flash point	< 0 °C (< 32 °F) Closed cup
Auto-ignition temperature	Not determined.
Decomposition temperature	Not determined.
pH	Not determined.
Kinematic viscosity	>= 0.4 - <= 0.9 cSt (40 °C (104 °F))
Solubility	
Solubility (water)	Not determined.
Partition coefficient (n-octanol/water) (log value)	Not determined.
Vapour pressure	<= 240 kPa (37.8 °C (100.04 °F))
Vapour pressure temp.	37.8 °C (100.04 °F)
Density and/or relative density	
Relative density	> 0.62 - < 0.88 (15 °C (59 °F))
Vapour density	Not determined.

<b>Particle characteristics</b>	Not applicable.
<b>9.2. Other information</b>	
<b>9.2.1. Information with regard to physical hazard classes</b>	No relevant additional information available.
<b>9.2.2. Other safety characteristics</b>	
<b>Viscosity</b>	< 1 mm <sup>2</sup> /s (37.8 °C (100.04 °F))

## SECTION 10: Stability and reactivity

<b>10.1. Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>10.2. Chemical stability</b>	Material is stable under normal conditions.
<b>10.3. Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>10.4. Conditions to avoid</b>	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>10.5. Incompatible materials</b>	Strong oxidising agents.
<b>10.6. Hazardous decomposition products</b>	No hazardous decomposition products are known.

## SECTION 11: Toxicological information

<b>General information</b>	Occupational exposure to the substance or mixture may cause adverse effects.
<b>Information on likely routes of exposure</b>	
<b>Inhalation</b>	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
<b>Skin contact</b>	Causes skin irritation.
<b>Eye contact</b>	Direct contact with eyes may cause temporary irritation.
<b>Ingestion</b>	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
<b>Symptoms</b>	Aspiration may cause pulmonary oedema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

<b>Acute toxicity</b>	May be fatal if swallowed and enters airways. Hydrogen sulphide, a highly toxic gas, may be present. Signs and symptoms of overexposure to hydrogen sulphide include respiratory and eye irritation, dizziness, nausea, coughing, a sensation of dryness and pain in the nose, and loss of consciousness. Odour does not provide a reliable indicator of the presence of hazardous levels in the atmosphere.
-----------------------	--

Product	Species	Test Results
Gasoline (CAS 86290-81-5)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg
<b>Inhalation</b>		
LC50	Rat	> 5610 mg/m <sup>3</sup> , 4 hours
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg
Impurities	Species	Test Results
Benzene (CAS 71-43-2)		
<b>Acute</b>		
<b>Oral</b>		
LD50	Rat	930 mg/kg
<b>Skin corrosion/irritation</b>	Causes skin irritation.	
<b>Serious eye damage/eye irritation</b>	Direct contact with eyes may cause temporary irritation.	
<b>Respiratory sensitisation</b>	Based on available data, the classification criteria are not met.	
<b>Skin sensitisation</b>	Based on available data, the classification criteria are not met.	
<b>Germ cell mutagenicity</b>	May cause genetic defects.	
<b>Carcinogenicity</b>	May cause cancer.	

## IARC Monographs. Overall Evaluation of Carcinogenicity

Benzene (CAS 71-43-2)

1 Carcinogenic to humans.

Gasoline (CAS 86290-81-5)

2B Possibly carcinogenic to humans.

<b>Reproductive toxicity</b>	Suspected of damaging fertility or the unborn child.
<b>Specific target organ toxicity - single exposure</b>	May cause drowsiness and dizziness.
<b>Specific target organ toxicity - repeated exposure</b>	Based on available data, the classification criteria are not met.
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.
<b>Mixture versus substance information</b>	No information available.

### 11.2. Information on other hazards

<b>Endocrine disrupting properties</b>	This mixture does not contain any substances having endocrine disrupting properties with respect to human health as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than 0.1% by weight.
<b>Other information</b>	May be absorbed through the skin.

## SECTION 12: Ecological information

**12.1. Toxicity** Toxic to aquatic life with long lasting effects.

Product	Species	Test Results
Gasoline (CAS 86290-81-5) <i>Acute</i>	EL50 Selenastrum capricornutum (Pseudokirchnerella subcapitata)	3.1 mg/l, 72 hours
<b>Aquatic</b> <i>Acute</i>		
Crustacea	EL50 Daphnia magna	4.5 mg/l, 48 hours
Fish	LL50 Oncorhynchus mykiss Pimephales promelas	10 mg/l, 96 hours 8.2 mg/l, 96 hours
Micro-organisms	LL50 Tetrahymena pyriformis	15.41 mg/l, 72 hours

**12.2. Persistence and degradability** Expected to be inherently biodegradable.

**12.3. Bioaccumulative potential** The product is not bioaccumulating.

**Partition coefficient n-octanol/water (log Kow)** Not available.

Benzene (CAS 71-43-2) 2.13

**Bioconcentration factor (BCF)** Not available.

**12.4. Mobility in soil** No data available.

**12.5. Results of PBT and vPvB assessment** This substance does not meet vPvB / PBT criteria of Regulation (EC) No 1907/2006, Annex XIII.

**12.6. Endocrine disrupting properties** This mixture does not contain any substances having endocrine disrupting properties with respect to the environment as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than 0.1% by weight.

**12.7. Other adverse effects** Oil spills are generally hazardous to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

<b>Residual waste</b>	Dispose in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
<b>EU waste code</b>	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Disposal methods/information** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Special precautions** Dispose in accordance with all applicable regulations.

## SECTION 14: Transport information

### ADR

14.1. UN number UN1203  
14.2. UN proper shipping name GASOLINE  
14.3. Transport hazard class(es)  
Class 3  
Subsidiary risk -  
Label(s) 3  
Hazard No. (ADR) 33  
Tunnel restriction code D/E  
14.4. Packing group II  
14.5. Environmental hazards Yes  
14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

### RID

14.1. UN number UN1203  
14.2. UN proper shipping name GASOLINE  
14.3. Transport hazard class(es)  
Class 3  
Subsidiary risk -  
Label(s) 3  
14.4. Packing group II  
14.5. Environmental hazards Yes  
14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

### ADN

14.1. UN number UN1203  
14.2. UN proper shipping name GASOLINE  
14.3. Transport hazard class(es)  
Class 3  
Subsidiary risk -  
Label(s) 3  
14.4. Packing group II  
14.5. Environmental hazards Yes  
14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

### IATA

14.1. UN number UN1203  
14.2. UN proper shipping name GASOLINE  
14.3. Transport hazard class(es)  
Class 3  
Subsidiary risk -  
14.4. Packing group II  
14.5. Environmental hazards Yes  
ERG Code 3H  
14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

### IMDG

14.1. UN number UN1203  
14.2. UN proper shipping name GASOLINE  
14.3. Transport hazard class(es)  
Class 3  
Subsidiary risk -  
14.4. Packing group II



#### 14.5. Environmental hazards

Marine pollutant Yes

EmS F-E, S-E

14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

14.7. Maritime transport in bulk according to IMO instruments Not applicable. However, this product is a liquid and if transported in bulk covered under MARPOL 73/78, Annex I.

General information Shipping descriptions in this section are offered as examples only. Classification for transport must accurately reflect the material hazards as designated under a variety of regulations and is solely the responsibility of the person offering the material for transport into commerce.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended  
Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended  
Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended  
Benzene (CAS 71-43-2)

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended  
Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended  
Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended  
Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended  
Benzene (CAS 71-43-2)

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA  
Not listed.

##### Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended  
Not listed.

##### Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended  
Benzene (CAS 71-43-2)  
Gasoline (CAS 86290-81-5)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Benzene (CAS 71-43-2)  
Gasoline (CAS 86290-81-5)

##### Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended  
Benzene (CAS 71-43-2)  
Gasoline (CAS 86290-81-5)

##### Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.  
Directive 2012/18/EU on major accident hazards involving dangerous substances: Part 2 (Named dangerous substances) - 34. Petroleum products and alternative fuels.

##### National regulations

According to Directive 92/85/EEC as amended, pregnant women should not work with the product, if there is the least risk of exposure.

Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended. Follow national regulation on the protection of workers from the risks of exposure to carcinogens and mutagens at work, in accordance with Directive 2004/37/EC, as amended.

##### 15.2. Chemical safety assessment

Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

### List of abbreviations

DNEL: Derived No-Effect Level.  
PNEC: Predicted No-Effect Concentration.  
PBT: Persistent, bioaccumulative and toxic.  
vPvB: Very Persistent and very Bioaccumulative.

### References

Chemical safety report.  
CONCAWE  
ECHA: European Chemical Agency.

### Information on evaluation method leading to the classification of mixture

Not applicable.

### Full text of any statements, which are not written out in full under sections 2 to 15

H224 Extremely flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H340 May cause genetic defects.  
H350 May cause cancer.  
H361 Suspected of damaging fertility or the unborn child.  
H411 Toxic to aquatic life with long lasting effects.

### Training information

Follow training instructions when handling this material.

### Disclaimer

The information in this Safety Data Sheet (SDS) was obtained from sources believed to be reliable and accurate, and is not represented as being absolutely complete. The end user of this product has the responsibility for evaluating the adequacy of the data for the intended application and conditions of use; for determining the safety, toxicity, regulatory requirements, and suitability of the product under these conditions; and for obtaining additional or clarifying data where uncertainty exists. The data serves as general guidance only, and is to be used in combination with professional judgement of persons experienced in a specific application, use or process; and additional data may be required.

## Annex to the extended Safety Data Sheet (eSDS)

### Table of contents

1. ES: Manufacture of substance (ERC1, PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC15)	12
2. ES: Formulation & (re)packing of substances and mixtures (SU10, ERC2, PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC15)	15
3. ES: Use as an intermediate (SU8, SU9, ERC6a, PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC15)	18
4. ES: Distribution of substance (ERC5, ERC4, ERC6a, ERC6b, ERC6c, ERC6d, ERC7, PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC15)	21
5. ES: Use as a fuel, Industrial (ERC9b, ERC9a, PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC16)	24
6. ES: Use as a fuel, Professional (SU22, ERC9b, ERC9a, PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC16)	27
7. ES: Use as a fuel, Consumer (SU21, ERC9b, ERC9a, PC13)	30

# 1 - Exposure Scenario Worker

## 1. Manufacture of substance

### List of use descriptors

Sector(s) of Use                      Manufacture of substance

Name of contributing environmental scenario and corresponding ERC                      ERC1: Manufacture of the substance

List of names of contributing worker scenarios and corresponding PROCs                      PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions  
PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions  
PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition  
PROC8a: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities  
PROC8b: Transfer of substance or mixture (charging/discharging) at dedicated facilities  
PROC15: Use as laboratory reagent

### 2.1.1. Contributing scenario controlling environmental exposure for Manufacture of the substance

#### Product characteristics

Physical state                      Liquid.  
Substance is complex UVCB. Predominantly hydrophobic

#### Amounts used

Fraction of EU tonnage used in region                      0.1  
Regional use tonnage                      11000000 tonnes/year  
Fraction of regional tonnage used locally                      0.45  
Annual site tonnage                      5200000 tonnes/year  
Annual amount per site                      17000000 kg/day

#### Frequency and duration of use

Continuous process                      300 days/year

#### Environment factors not influenced by risk management

Local freshwater dilution factor:                      10  
Local marine water dilution factor:                      100

#### Other given operational conditions affecting environmental exposure

Type	Emission days (days/year)	Emission factors			Remarks
		Air	Soil	Water	
initial release prior to RMM	300	0.0066	0.0001	0.00004	

#### Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release                      Common practices vary across sites thus conservative process release estimates used.

#### Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Air                      Treat air emission to provide a typical removal efficiency of (%): 90  
Soil                      Not applicable.  
Water                      Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of  $\geq$  (%): 95.1. If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of  $\geq$  (%): 0.  
Sediment                      Not applicable.

Organisational measures to prevent/limit release from site                      Risk from environmental exposure is driven by freshwater sediment. Prevent discharge of undissolved substance to or recover from onsite wastewater. If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.

#### Conditions and measures related to municipal sewage treatment plant

##### Size of municipal sewage system/treatment plant (m3/d)

Type                      Municipal Sewage Treatment Plant  
Discharge rate                      1000 m<sup>3</sup>/day

<b>Treatment effectiveness</b>	95.5 %
<b>Sludge treatment technique</b>	Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.
<b>Remarks</b>	Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal 1.9e7 kg/d
<b>Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)</b>	95.5 %

#### Conditions and measures related to external treatment of waste for disposal

##### Fraction of used amount transferred to external waste treatment

<b>Suitable waste treatment</b>	During manufacturing no waste of the substance is generated.
<b>Disposal methods</b>	Not applicable.
<b>Treatment effectiveness</b>	Not available.

#### Conditions and measures related to external recovery of waste

##### Fraction of used amount transferred to external waste treatment

<b>Suitable recover operations</b>	During manufacturing no waste of the substance is generated.
------------------------------------	--

### 2.2.1. Contributing scenario controlling worker exposure for Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions

#### Product characteristics

<b>Physical form of the product</b>	Liquid
<b>vapour pressure</b>	Liquid, vapour pressure > 10 kPa at Standard Temperature and Pressure

#### Amounts used

Covers percentage substance in the product up to 100 %.

#### Frequency and duration of use

Covers daily exposures up to 8 hours

#### Human factors not influenced by risk management

#### Other given operational conditions affecting workers exposure

Assumes a good basic standard of occupational hygiene is implemented.

#### Other relevant operational conditions

Operation is carried out at elevated temperature (> 20°C above ambient temperature)

#### Risk management measures (RMM)

<b>Technical conditions and measures at process level (source) to prevent release</b>	General exposures (closed systems) with sample collection: Handle substance within a closed system. Sample via a closed loop or other system to avoid exposure.
	General exposures (closed systems) Continuous process: Handle substance within a closed system.
	General exposures (closed systems) Batch process: Handle substance within a closed system. Ensure operation is undertaken outdoors.
<b>Technical conditions and measures to control dispersion from source towards the worker</b>	Storage: Ensure operation is undertaken outdoors. Store substance within a closed system.
	Laboratory activities: Handle within a fume cupboard or implement suitable equivalent methods to minimise exposure. Bulk transfers: Ensure material transfers are under containment or extract ventilation.

**Organizational measures to prevent/limit releases, dispersion and exposure**

General measures (carcinogens): Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance.

Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and dispose of wastes safely.

Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures.

Consider the need for risk based health surveillance.

Equipment cleaning and maintenance: Drain down and flush system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Clear spills immediately.

**Conditions and measures related to personal protection, hygiene and health evaluations**

General measures (skin irritants): Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

General exposures (closed systems) with sample collection: Wear suitable gloves tested to EN374.

Equipment cleaning and maintenance: Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.

### 3. Exposure Estimation

#### Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

#### Health

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

### 4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

#### Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

#### Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. Available hazard data do not support the need for a DNEL to be established for other health effects. Risk Management Measures are based on qualitative risk characterisation.

## 2 - Exposure Scenario Worker

### 1. Formulation & (re)packing of substances and mixtures

#### List of use descriptors

**Sector(s) of Use** SU10: Formulation [mixing] of preparations and/or re-packaging

**Name of contributing environmental scenario and corresponding ERC** ERC2: Formulation into mixture

**List of names of contributing worker scenarios and corresponding PROCs**

PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions  
 PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions  
 PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition  
 PROC8a: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities  
 PROC8b: Transfer of substance or mixture (charging/discharging) at dedicated facilities  
 PROC15: Use as laboratory reagent

#### 2.1.1. Contributing scenario controlling environmental exposure for Formulation into mixture

##### Product characteristics

**Physical state** Liquid.  
 Substance is complex UVCB. Predominantly hydrophobic

##### Amounts used

**Fraction of EU tonnage used in region** 0.1  
**Regional use tonnage** 10000000 tonnes/year  
**Fraction of regional tonnage used locally** 0.003  
**Annual site tonnage** 30000 tonnes/year  
**Maximum daily site tonnage** 100000 kg/day

##### Frequency and duration of use

**Continuous process** 300 days/year

##### Environment factors not influenced by risk management

**Local freshwater dilution factor:** 10  
**Local marine water dilution factor:** 100

##### Other given operational conditions affecting environmental exposure

Type	Emission days (days/year)	Emission factors			Remarks
		Air	Soil	Water	
initial release prior to RMM	300	0.025	0.0001	0.0014	

##### Risk management measures (RMM)

**Technical conditions and measures at process level (source) to prevent release** Common practices vary across sites thus conservative process release estimates used.

##### Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

**Air** Treat air emission to provide a typical removal efficiency of (%): 0  
**Soil** Not applicable.  
**Water** Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of  $\geq$  (%): 95.1. If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of  $\geq$  (%): 0.  
**Sediment** Not applicable.

**Organisational measures to prevent/limit release from site** Risk from environmental exposure is driven by freshwater sediment. Prevent discharge of undissolved substance to or recover from onsite wastewater. If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.

##### Conditions and measures related to municipal sewage treatment plant

##### Size of municipal sewage system/treatment plant (m3/d)

**Type** Municipal Sewage Treatment Plant  
**Discharge rate** 2000 m<sup>3</sup>/day

<b>Treatment effectiveness</b>	95.5 %
<b>Sludge treatment technique</b>	Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.
<b>Remarks</b>	Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal 1.1e5 kg/d
<b>Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)</b>	95.5 %

#### Conditions and measures related to external treatment of waste for disposal

##### Fraction of used amount transferred to external waste treatment

<b>Suitable waste treatment</b>	External treatment and disposal of waste should comply with applicable local and/or national regulations.
<b>Disposal methods</b>	Not applicable.
<b>Treatment effectiveness</b>	Not available.

#### Conditions and measures related to external recovery of waste

##### Fraction of used amount transferred to external waste treatment

<b>Suitable recover operations</b>	External recovery and recycling of waste should comply with applicable local and/or national regulations.
------------------------------------	---

### 2.2.1. Contributing scenario controlling worker exposure for Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions

#### Product characteristics

<b>Physical form of the product</b>	Liquid.
<b>vapour pressure</b>	Liquid, vapour pressure > 10 kPa at Standard Temperature and Pressure

#### Amounts used

Covers percentage substance in the product up to 100 %.

#### Frequency and duration of use

Covers daily exposures up to 8 hours

#### Human factors not influenced by risk management

##### Other given operational conditions affecting workers exposure

Assumes a good basic standard of occupational hygiene is implemented.

##### Other relevant operational conditions

Assumes use at not more than 20°C above ambient temperature, unless stated differently.

#### Risk management measures (RMM)

**Technical conditions and measures at process level (source) to prevent release** General exposures (closed systems) With sample collection: Handle substance within a closed system. Sample via a closed loop or other system to avoid exposure.

General exposures (closed systems), Outdoor.: Handle substance within a closed system.

Storage: Store substance within a closed system.

**Technical conditions and measures to control dispersion from source towards the worker** Process sampling: Sample via a closed loop or other system to avoid exposure.

Bulk transfers: Ensure material transfers are under containment or extract ventilation.

Drum/batch transfers: Ensure material transfers are under containment or extract ventilation.

Laboratory activities: Handle within a fume cupboard or implement suitable equivalent methods to minimise exposure.



**Organizational measures to prevent/limit releases, dispersion and exposure**

General measures (carcinogens): Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance.

Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and dispose of wastes safely.

Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures.

Consider the need for risk based health surveillance.

Equipment cleaning and maintenance: Drain down and flush system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Clear spills immediately.

**Conditions and measures related to personal protection, hygiene and health evaluations**

General measures (skin irritants): Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

General exposures (closed systems) with sample collection: Wear suitable gloves tested to EN374.

Equipment cleaning and maintenance: Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.

Storage: Wear suitable gloves tested to EN374.

### 3. Exposure Estimation

#### Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

#### Health

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

### 4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

#### Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

#### Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. Available hazard data enable the derivation of a DNEL for other health effects. Risk Management Measures are based on qualitative risk characterisation.

### 3 - Exposure Scenario Worker

#### 1. Use as an intermediate

##### List of use descriptors

**Sector(s) of Use** SU8: Manufacture of bulk, large scale chemicals (including petroleum products)  
SU9: Manufacture of fine chemicals

**Name of contributing environmental scenario and corresponding ERC** ERC6a: Use of intermediate

**List of names of contributing worker scenarios and corresponding PROCs** PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions  
PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions  
PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition  
PROC8a: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities  
PROC8b: Transfer of substance or mixture (charging/discharging) at dedicated facilities  
PROC15: Use as laboratory reagent

#### 2.1.1. Contributing scenario controlling environmental exposure for Use of intermediate

##### Product characteristics

**Physical state** Liquid.  
Substance is complex UVCB. Predominantly hydrophobic

##### Amounts used

**Fraction of EU tonnage used in region** 0.1  
**Regional use tonnage** 630000 tonnes/year  
**Fraction of regional tonnage used locally** 0.024  
**Annual site tonnage** 15000 tonnes/year  
**Maximum daily site tonnage** 50000 kg/day

##### Frequency and duration of use

**Batch process** Not applicable.  
**Continuous process** 300 days/year

##### Environment factors not influenced by risk management

**Local freshwater dilution factor:** 10  
**Local marine water dilution factor:** 100

##### Other given operational conditions affecting environmental exposure

Type	Emission days (days/year)	Emission factors			Remarks
		Air	Soil	Water	
initial release prior to RMM	300	0.025	0.001	0.003	

##### Risk management measures (RMM)

**Technical conditions and measures at process level (source) to prevent release** Common practices vary across sites thus conservative process release estimates used.

##### Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

**Air** Treat air emission to provide a typical removal efficiency of (%): 80  
**Soil** Not applicable.  
**Water** Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of  $\geq$  (%): 95.5. If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of  $\geq$  (%): 0.  
**Sediment** Not applicable.  
**Remarks** Not applicable.

**Organisational measures to prevent/limit release from site** Risk from environmental exposure is driven by freshwater sediment. Prevent discharge of undissolved substance to or recover from onsite wastewater. If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.

##### Conditions and measures related to municipal sewage treatment plant

### Size of municipal sewage system/treatment plant (m3/d)

Type	Municipal Sewage Treatment Plant
Discharge rate	2000 m <sup>3</sup> /day
Treatment effectiveness	95.5 %
Sludge treatment technique	Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.
Remarks	Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal 5.1e4 kg/d
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	95.5 %

### Conditions and measures related to external treatment of waste for disposal

#### Fraction of used amount transferred to external waste treatment

Suitable waste treatment	This substance is consumed during use and no waste of the substance is generated.
Disposal methods	Not applicable.
Treatment effectiveness	Not available.
Remarks	Not applicable.

### Conditions and measures related to external recovery of waste

#### Fraction of used amount transferred to external waste treatment

Suitable recover operations	This substance is consumed during use and no waste of the substance is generated.
Remarks	Not applicable.

## 2.2.1. Contributing scenario controlling worker exposure for Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions

### Product characteristics

Physical form of the product	Liquid.
vapour pressure	Liquid, vapour pressure > 10 kPa at Standard Temperature and Pressure

### Amounts used

Covers percentage substance in the product up to 100 %.

### Frequency and duration of use

Covers daily exposures up to 8 hours

### Human factors not influenced by risk management

#### Other given operational conditions affecting workers exposure

Assumes a good basic standard of occupational hygiene is implemented.

#### Other relevant operational conditions

Operation is carried out at elevated temperature (> 20°C above ambient temperature)

### Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release	General exposures (closed systems) with sample collection: Handle substance within a closed system. Sample via a closed loop or other system to avoid exposure.
	General exposures (closed systems): Handle substance within a closed system. Ensure operation is undertaken outdoors.
Technical conditions and measures to control dispersion from source towards the worker	Laboratory activities: Handle within a fume cupboard or implement suitable equivalent methods to minimise exposure.
	Bulk transfers: Ensure material transfers are under containment or extract ventilation.
	Storage: Store substance within a closed system. Ensure operation is undertaken outdoors.

**Organizational measures to prevent/limit releases, dispersion and exposure**

General measures (carcinogens): Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance.

Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and dispose of wastes safely.

Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures.  
Consider the need for risk based health surveillance.

Equipment cleaning and maintenance: Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Clear spills immediately.

**Conditions and measures related to personal protection, hygiene and health evaluations**

General measures (skin irritants) Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

General exposures (closed systems) with sample collection: Wear suitable gloves tested to EN374.

Equipment cleaning and maintenance: Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.

### 3. Exposure Estimation

#### Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

#### Health

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

### 4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

#### Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

#### Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. Available hazard data enable the derivation of a DNEL for other health effects. Risk Management Measures are based on qualitative risk characterisation.

## 4 - Exposure Scenario Worker

### 1. Distribution of substance

#### List of use descriptors

<b>Sector(s) of Use</b>	Distribution of substance
<b>Name of contributing environmental scenario and corresponding ERC</b>	ERC4: Use of non-reactive processing aid at industrial site (no inclusion into or onto article) ERC5: Use at industrial site leading to inclusion into/onto article ERC6a: Use of intermediate ERC6b: Use of reactive processing aid at industrial site (no inclusion into or onto article) ERC6c: Use of monomer in polymerisation processes at industrial site (inclusion or not into/onto article) ERC6d: Use of reactive process regulators in polymerisation processes at industrial site (inclusion or not into/onto article) ERC7: Use of functional fluid at industrial site

#### List of names of contributing worker scenarios and corresponding PROCs

PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions  
 PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions  
 PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition  
 PROC8a: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities  
 PROC8b: Transfer of substance or mixture (charging/discharging) at dedicated facilities  
 PROC15: Use as laboratory reagent

### 2.1.1. Contributing scenario controlling environmental exposure for Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

#### Product characteristics

**Physical state** Liquid.  
 Substance is complex UVCB. Predominantly hydrophobic

#### Amounts used

**Fraction of EU tonnage used in region** 0.1  
**Regional use tonnage** 11000000 tonnes/year  
**Fraction of regional tonnage used locally** 0.002  
**Annual site tonnage** 22000 tonnes/year  
**Maximum daily site tonnage** 72000 kg/day

#### Frequency and duration of use

**Continuous process** 300 days/year

#### Environment factors not influenced by risk management

**Local freshwater dilution factor:** 10  
**Local marine water dilution factor:** 100

#### Other given operational conditions affecting environmental exposure

Type	Emission days (days/year)	Emission factors			Remarks
		Air	Soil	Water	
initial release prior to RMM	300	0.001	0.00001	0.00001	

#### Risk management measures (RMM)

**Technical conditions and measures at process level (source) to prevent release** Common practices vary across sites thus conservative process release estimates used.

#### Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

**Air** Treat air emission to provide a typical removal efficiency of (%): 90  
**Soil** Not applicable.  
**Water** Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of  $\geq$  (%): 0. If discharging to municipal sewage treatment plant, provide the required onsite wastewater removal efficiency of  $\geq$  (%): 0  
**Sediment** Not applicable.

**Organisational measures to prevent/limit release from site** Risk from environmental exposure is driven by freshwater. No wastewater treatment required.

#### Conditions and measures related to municipal sewage treatment plant

##### Size of municipal sewage system/treatment plant (m<sup>3</sup>/d)

Type	Municipal Sewage Treatment Plant
Discharge rate	2000 m <sup>3</sup> /day
Treatment effectiveness	95.5 %
Sludge treatment technique	Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.
Remarks	Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal 3.3e6 kg/d
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	95.5 %

#### Conditions and measures related to external treatment of waste for disposal

##### Fraction of used amount transferred to external waste treatment

Suitable waste treatment	External treatment and disposal of waste should comply with applicable local and/or national regulations.
Disposal methods	Not applicable.
Treatment effectiveness	Not available.

#### Conditions and measures related to external recovery of waste

##### Fraction of used amount transferred to external waste treatment

Suitable recover operations	External recovery and recycling of waste should comply with applicable local and/or national regulations.
-----------------------------	---

## 2.2.1. Contributing scenario controlling worker exposure for Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions

#### Product characteristics

Physical form of the product	Liquid.
vapour pressure	Liquid, vapour pressure > 10 kPa at Standard Temperature and Pressure

#### Amounts used

Covers percentage substance in the product up to 100 %.

#### Frequency and duration of use

Covers daily exposures up to 8 hours

#### Human factors not influenced by risk management

#### Other given operational conditions affecting workers exposure

Assumes a good basic standard of occupational hygiene is implemented.

#### Other relevant operational conditions

Assumes use at not more than 20°C above ambient temperature, unless stated differently.

#### Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release	General exposures (closed systems) with sample collection: Handle substance within a closed system. Sample via a closed loop or other system to avoid exposure.
	General exposures (closed systems) Outdoor.: Handle substance within a closed system.
	Storage: Ensure operation is undertaken outdoors. Store substance within a closed system.
Technical conditions and measures to control dispersion from source towards the worker	Process sampling: Sample via a closed loop or other system to avoid exposure.
	Laboratory activities: Handle within a fume cupboard or implement suitable equivalent methods to minimise exposure.
	Bulk closed loading and unloading: Ensure material transfers are under containment or extract ventilation.

**Organizational measures to prevent/limit releases, dispersion and exposure**

General measures (carcinogens): Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance.

Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and dispose of wastes safely.

Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures.

Consider the need for risk based health surveillance.

Equipment cleaning and maintenance: Drain down and flush system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Clear spills immediately.

**Conditions and measures related to personal protection, hygiene and health evaluations**

General measures (skin irritants): Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

General exposures (closed systems) with sample collection: Wear suitable gloves tested to EN374.

Equipment cleaning and maintenance: Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.

### 3. Exposure Estimation

#### Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

#### Health

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

### 4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

#### Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

#### Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. Available hazard data do not enable the derivation of a DNEL for carcinogenic effects. Available hazard data enable the derivation of a DNEL for other health effects. Risk Management Measures are based on qualitative risk characterisation.

## 5 - Exposure Scenario Worker

### 1. Use as a fuel, Industrial

#### List of use descriptors

<b>Sector(s) of Use</b>	Industrial uses
<b>Name of contributing environmental scenario and corresponding ERC</b>	ERC9a: Widespread use of functional fluid (indoor) ERC9b: Widespread use of functional fluid (outdoor)
<b>List of names of contributing worker scenarios and corresponding PROCs</b>	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition PROC8a: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities PROC8b: Transfer of substance or mixture (charging/discharging) at dedicated facilities PROC16: Use of fuels

#### 2.1.1. Contributing scenario controlling environmental exposure for Widespread use of functional fluid (indoor)

##### Product characteristics

<b>Physical state</b>	Liquid. Substance is complex UVCB. Predominantly hydrophobic
-----------------------	---

##### Amounts used

<b>Fraction of EU tonnage used in region</b>	0.1
<b>Regional use tonnage</b>	1000000 tonnes/year
<b>Fraction of regional tonnage used locally</b>	1
<b>Annual site tonnage</b>	1000000 tonnes/year
<b>Maximum daily site tonnage</b>	3300000 kg/day

##### Frequency and duration of use

<b>Continuous process</b>	300 days/year
---------------------------	---------------

##### Environment factors not influenced by risk management

<b>Local freshwater dilution factor:</b>	10
<b>Local marine water dilution factor:</b>	100

##### Other given operational conditions affecting environmental exposure

Type	Emission days (days/year)	Emission factors			Remarks
		Air	Soil	Water	
initial release prior to RMM	300	0.05	0	0.00001	

##### Risk management measures (RMM)

<b>Technical conditions and measures at process level (source) to prevent release</b>	Common practices vary across sites thus conservative process release estimates used.
---	--

##### Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

<b>Air</b>	Treat air emission to provide a typical removal efficiency of (%): 95
<b>Soil</b>	Not applicable.
<b>Water</b>	Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of $\geq$ (%): 79.8. If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of $\geq$ (%): 0
<b>Sediment</b>	Not applicable.

<b>Organisational measures to prevent/limit release from site</b>	Risk from environmental exposure is driven by humans via indirect exposure (primarily inhalation). If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.
---	--

##### Conditions and measures related to municipal sewage treatment plant

##### Size of municipal sewage system/treatment plant (m3/d)

<b>Type</b>	Municipal Sewage Treatment Plant
<b>Discharge rate</b>	2000 m <sup>3</sup> /day



<b>Treatment effectiveness</b>	95.5 %
<b>Sludge treatment technique</b>	Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.
<b>Remarks</b>	Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal 5.4e6 kg/d
<b>Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)</b>	95.5 %

#### Conditions and measures related to external treatment of waste for disposal

##### Fraction of used amount transferred to external waste treatment

<b>Suitable waste treatment</b>	Combustion emissions limited by required exhaust emission controls. Combustion emissions considered in regional exposure assessment. External treatment and disposal of waste should comply with applicable local and/or national regulations.
<b>Disposal methods</b>	Not applicable.
<b>Treatment effectiveness</b>	Not available.

#### Conditions and measures related to external recovery of waste

##### Fraction of used amount transferred to external waste treatment

<b>Suitable recover operations</b>	This substance is consumed during use and no waste of the substance is generated.
------------------------------------	---

### 2.2.1. Contributing scenario controlling worker exposure for Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions

#### Product characteristics

<b>Physical form of the product</b>	Liquid.
<b>vapour pressure</b>	Liquid, vapour pressure > 10 kPa at Standard Temperature and Pressure

#### Amounts used

Covers percentage substance in the product up to 100 %.

#### Frequency and duration of use

Covers daily exposures up to 8 hours

#### Human factors not influenced by risk management

##### Other given operational conditions affecting workers exposure

Assumes a good basic standard of occupational hygiene is implemented.

##### Other relevant operational conditions

Assumes use at not more than 20°C above ambient temperature, unless stated differently.

#### Risk management measures (RMM)

<b>Technical conditions and measures at process level (source) to prevent release</b>	<p>General exposures (closed systems): Handle substance within a closed system. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.</p> <p>Use as a fuel (closed systems): Handle substance within a closed system.</p> <p>Storage: Store substance within a closed system. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.</p>
<b>Technical conditions and measures to control dispersion from source towards the worker</b>	<p>Drum/batch transfers: Ensure material transfers are under containment or extract ventilation.</p> <p>Refuelling: Ensure material transfers are under containment or extract ventilation.</p> <p>Refuelling aircraft: Ensure material transfers are under containment or extract ventilation.</p> <p>Bulk closed unloading: Ensure material transfers are under containment or extract ventilation.</p>

**Organizational measures to prevent/limit releases, dispersion and exposure**

General measures (carcinogens): Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance.

Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and dispose of wastes safely.

Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures.

Consider the need for risk based health surveillance.

Equipment cleaning and maintenance: Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Clear spills immediately. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.

**Conditions and measures related to personal protection, hygiene and health evaluations**

General measures (skin irritants): Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely.

Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

Equipment cleaning and maintenance: Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.

### 3. Exposure Estimation

#### Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

#### Health

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

### 4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

#### Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

#### Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. Available hazard data enable the derivation of a DNEL for other health effects. Risk Management Measures are based on qualitative risk characterisation.

## 6 - Exposure Scenario Worker

### 1. Use as a fuel, Professional

#### List of use descriptors

<b>Sector(s) of Use</b>	SU22: Professional uses
<b>Name of contributing environmental scenario and corresponding ERC</b>	ERC9a: Widespread use of functional fluid (indoor) ERC9b: Widespread use of functional fluid (outdoor)
<b>List of names of contributing worker scenarios and corresponding PROCs</b>	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition PROC8a: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities PROC8b: Transfer of substance or mixture (charging/discharging) at dedicated facilities PROC16: Use of fuels

#### 2.1.1. Contributing scenario controlling environmental exposure for Widespread use of functional fluid (indoor)

##### Product characteristics

**Physical state** Liquid.  
Substance is complex UVCB. Predominantly hydrophobic

##### Amounts used

<b>Fraction of EU tonnage used in region</b>	0.1
<b>Regional use tonnage</b>	960000 tonnes/year
<b>Fraction of regional tonnage used locally</b>	0.0005
<b>Annual site tonnage</b>	480 tonnes/year
<b>Maximum daily site tonnage</b>	1300 kg/day

##### Frequency and duration of use

**Continuous process** Emission days (days/year): 365

##### Environment factors not influenced by risk management

<b>Local freshwater dilution factor:</b>	10
<b>Local marine water dilution factor:</b>	100

##### Other given operational conditions affecting environmental exposure

Type	Emission days (days/year)	Emission factors			Remarks
		Air	Soil	Water	
initial release prior to RMM	365	0.01	0.00001	0.00001	

##### Risk management measures (RMM)

**Technical conditions and measures at process level (source) to prevent release** Common practices vary across sites thus conservative process release estimates used.

##### Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

<b>Air</b>	Not applicable.
<b>Soil</b>	Not applicable.
<b>Water</b>	Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of $\geq$ (%): 0. If discharging to municipal sewage treatment plant, provide the required onsite wastewater removal efficiency of $\geq$ (%): 0
<b>Sediment</b>	Not applicable.

**Organisational measures to prevent/limit release from site** Risk from environmental exposure is driven by freshwater. No wastewater treatment required.

##### Conditions and measures related to municipal sewage treatment plant

##### Size of municipal sewage system/treatment plant (m3/d)

<b>Type</b>	Municipal Sewage Treatment Plant
<b>Discharge rate</b>	2000 m <sup>3</sup> /day

<b>Treatment effectiveness</b>	95.5 %
<b>Sludge treatment technique</b>	Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.
<b>Remarks</b>	Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal 7.1e4 kg/d
<b>Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)</b>	95.5 %

#### Conditions and measures related to external treatment of waste for disposal

##### Fraction of used amount transferred to external waste treatment

<b>Suitable waste treatment</b>	Combustion emissions limited by required exhaust emission controls. Combustion emissions considered in regional exposure assessment. External treatment and disposal of waste should comply with applicable local and/or national regulations.
<b>Disposal methods</b>	Not applicable.
<b>Treatment effectiveness</b>	Not available.

#### Conditions and measures related to external recovery of waste

##### Fraction of used amount transferred to external waste treatment

<b>Suitable recover operations</b>	This substance is consumed during use and no waste of the substance is generated.
------------------------------------	---

## 2.2.1. Contributing scenario controlling worker exposure for Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions

#### Product characteristics

<b>Physical form of the product</b>	Liquid.
<b>vapour pressure</b>	Liquid, vapour pressure > 10 kPa at Standard Temperature and Pressure

#### Amounts used

Covers percentage substance in the product up to 100 %.

#### Frequency and duration of use

Covers daily exposures up to 8 hours

#### Human factors not influenced by risk management

##### Other given operational conditions affecting workers exposure

Assumes a good basic standard of occupational hygiene is implemented.

##### Other relevant operational conditions

Assumes use at not more than 20°C above ambient temperature, unless stated differently.

#### Risk management measures (RMM)

<b>Technical conditions and measures at process level (source) to prevent release</b>	General exposures (closed systems) with sample collection: Handle substance within a closed system. Sample via a closed loop or other system to avoid exposure.
	General exposures (closed systems) Outdoor.: Handle substance within a closed system.
	Storage: Ensure operation is undertaken outdoors. Store substance within a closed system.
<b>Technical conditions and measures to control dispersion from source towards the worker</b>	Process sampling: Sample via a closed loop or other system to avoid exposure.
	Laboratory activities: Handle within a fume cupboard or implement suitable equivalent methods to minimise exposure.
	Bulk closed loading and unloading: Ensure material transfers are under containment or extract ventilation.

**Organizational measures to prevent/limit releases, dispersion and exposure**

General measures (carcinogens): Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance.

Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and dispose of wastes safely.

Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures.

Consider the need for risk based health surveillance.

Equipment cleaning and maintenance: Drain down and flush system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Clear spills immediately.

**Conditions and measures related to personal protection, hygiene and health evaluations**

General measures (skin irritants): Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

General exposures (closed systems) with sample collection: Wear suitable gloves tested to EN374.

Equipment cleaning and maintenance: Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.

### 3. Exposure Estimation

#### Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

#### Health

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

### 4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

#### Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

#### Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. Available hazard data enable the derivation of a DNEL for other health effects. Risk Management Measures are based on qualitative risk characterisation.

## 7 - Exposure Scenario Worker

### 1. Use as a fuel, Consumer

#### List of use descriptors

Sector(s) of Use	SU21: Consumer uses
Name of contributing environmental scenario and corresponding ERC	ERC9a: Widespread use of functional fluid (indoor) ERC9b: Widespread use of functional fluid (outdoor)
List of names of contributing worker scenarios and corresponding PROCs	PC13: Fuels

#### 2.1.1. Contributing scenario controlling environmental exposure for Widespread use of functional fluid (indoor)

##### Product characteristics

Physical state Liquid.

##### Amounts used

Fraction of EU tonnage used in region	0.1
Regional use tonnage	8200000 tonnes/year
Fraction of regional tonnage used locally	0.0005
Annual site tonnage	4100 tonnes/year
Maximum daily site tonnage	11000 kg/day

##### Frequency and duration of use

Continuous process Emission days (days/year): 365

##### Environment factors not influenced by risk management

Local freshwater dilution factor:	10
Local marine water dilution factor:	100

##### Other given operational conditions affecting environmental exposure

Type	Emission days (days/year)	Emission factors			Remarks
		Air	Soil	Water	
initial release prior to RMM	365	0.01	0.00001	0.00001	

##### Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release Not available.

##### Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Air	Not available.
Soil	Not available.
Water	Not available.
Sediment	Not available.

Organisational measures to prevent/limit release from site Not available.

##### Conditions and measures related to municipal sewage treatment plant

##### Size of municipal sewage system/treatment plant (m3/d)

Type	Municipal Sewage Treatment Plant
Discharge rate	2000 m <sup>3</sup> /day
Treatment effectiveness	95.5 %
Sludge treatment technique	Not available.
Remarks	Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal 5.9e5 kg/d

##### Conditions and measures related to external treatment of waste for disposal

### Fraction of used amount transferred to external waste treatment

<b>Suitable waste treatment</b>	Combustion emissions limited by required exhaust emission controls. Combustion emissions considered in regional exposure assessment. External treatment and disposal of waste should comply with applicable local and/or national regulations.
<b>Disposal methods</b>	Not applicable.
<b>Treatment effectiveness</b>	Not available.

### Conditions and measures related to external recovery of waste

### Fraction of used amount transferred to external waste treatment

<b>Suitable recover operations</b>	This substance is consumed during use and no waste of the substance is generated.
------------------------------------	---

## 2.2.1. Contributing scenario controlling worker exposure for Fuels

### Product characteristics

<b>Physical form of the product</b>	Liquid.
<b>vapour pressure</b>	Liquid, vapour pressure > 10 kPa at Standard Temperature and Pressure
<b>Process temperature</b>	Assumes activities are at ambient temperature (unless stated differently).

### Amounts used

<b>Liquid: automotive refuelling</b>	< 37500 g Covers percentage substance in the product up to 1 %.
<b>Liquid: scooter refuelling</b>	< 3750 g Covers percentage substance in the product up to 1 %.
<b>Liquid: garden equipment - use</b>	< 750 g Covers percentage substance in the product up to 1 %.
<b>Liquid: garden equipment - refuelling</b>	< 750 g Covers percentage substance in the product up to 1 %.

### Frequency and duration of use

	<b>Duration</b>	<b>Frequency of use</b>	<b>Remarks</b>
Liquid: automotive refuelling	< 0.05	52 days per year	(Duration unit = hour)
Liquid: scooter refuelling	< 0.03	52 days per year	(Duration unit = hour)
Liquid: garden equipment - use	< 2	26 days per year	(Duration unit = hour)
Liquid: garden equipment - refuelling	< 0.03	26 days per year	(Duration unit = hour)

### Human factors not influenced by risk management

<b>Exposed skin areas</b>	Liquid: automotive refuelling Covers skin contact area up to 210 cm <sup>2</sup> Liquid: scooter refuelling Covers skin contact area up to 210 cm <sup>2</sup> Liquid: garden equipment - refuelling Covers skin contact area up to 420 cm <sup>2</sup>
---------------------------	---

### Other given operational conditions affecting workers exposure

<b>Area of use</b>	<b>Room size</b>	<b>Temperature</b>	<b>Ventilation rate</b>	<b>Remarks</b>
Liquid: automotive refuelling	100 m <sup>3</sup>			Outdoor use
Liquid: scooter refuelling	100 m <sup>3</sup>			Outdoor use
Liquid: garden equipment - use	100 m <sup>3</sup>			Outdoor use
Liquid: garden equipment - refuelling	34 m <sup>3</sup>			Indoor use

### Other relevant operational conditions

Not available.

### Risk management measures (RMM)

<b>Technical conditions and measures to control dispersion from source towards the worker</b>	Not available.
<b>Organizational measures to prevent/limit releases, dispersion and exposure</b>	Not available.
<b>Conditions and measures related to personal protection, hygiene and health evaluations</b>	Not available.

### **3. Exposure Estimation**

#### **Environment**

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

#### **Health**

The ECETOC TRA tool has been used to estimate consumer exposures, consistent with the content of ECETOC report #107 and the chapter R15 of the IR&CSA TGD. Where exposure determinants differ to these source, then they are indicated.

### **4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES**

#### **Environment**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

#### **Health**

Predicted exposures are not expected to exceed the applicable consumer reference values when the operational conditions/risk management measures given in section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.