



# SAFETY DATA SHEET

## 1. Identification

<b>Product identifier</b>	<b>Cat Gasoline</b>
<b>Other means of identification</b>	
<b>SDS number</b>	004-GHS
<b>Synonyms</b>	Light Catalytic Cracked Naphtha See section 16 for complete information.
<b>Recommended use</b>	Motor Fuel Motor fuels.
<b>Recommended restrictions</b>	None known.
<b>Manufacturer/Importer/Supplier/Distributor information</b>	
<b>Manufacturer/Supplier</b>	Valero Marketing & Supply Company and Affiliates One Valero Way San Antonio, TX 78269-6000 210-345-4593
<b>General Assistance</b>	
<b>E-Mail</b>	CorpHSE@valero.com
<b>Contact Person</b>	Industrial Hygienist
<b>Emergency Telephone</b>	24 Hour Emergency 866-565-5220 1-800-424-9300 (CHEMTREC USA)

## 2. Hazard(s) identification

<b>Physical hazards</b>	Flammable liquids	Category 1
<b>Health hazards</b>	Acute toxicity, inhalation	Category 4
	Skin corrosion/irritation	Category 2
	Germ cell mutagenicity	Category 1B
	Carcinogenicity	Category 1B
	Reproductive toxicity	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2
	Aspiration hazard	Category 1
<b>Environmental hazards</b>	Hazardous to the aquatic environment, long-term hazard	Category 2
<b>OSHA defined hazards</b>	Not classified.	
<b>Label elements</b>		



<b>Signal word</b>	Danger
<b>Hazard statement</b>	Extremely flammable liquid and vapor. Harmful if inhaled. Causes skin irritation. May cause genetic defects. May cause cancer. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs (blood, liver, kidney) through prolonged or repeated exposure. May be fatal if swallowed and enters airways.

<b>Precautionary statement</b>	
<b>Prevention</b>	Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area.

**Response**

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. If swallowed: Immediately call a poison center/doctor. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Take off contaminated clothing and wash before reuse.

**Storage**

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

**Disposal**

Dispose of contents/container in accordance with local/regional/national/international regulations.

**Hazard(s) not otherwise classified (HNOC)**

None known.

**3. Composition/information on ingredients****Mixtures**

Chemical name	CAS number	%
Naphtha (petroleum), light catalytic cracked	64741-55-5	0 - 100
Hexane (Other Isomers)	96-14-0	0 - 30
Toluene	108-88-3	0 - 10
Xylene (o, m, p isomers)	1330-20-7	0 - 10
1,2,4-Trimethylbenzene	95-63-6	0 - 5
Benzene	71-43-2	0 - 5
Butylene	25167-67-3	0 - 5
Cumene	98-82-8	0 - 5
Cyclohexane	110-82-7	0 - 5
Ethylbenzene	100-41-4	0 - 5
Pentane	109-66-0	0 - 5
n-Heptane	142-82-5	0 - 3
n-Hexane	110-54-3	0 - 3
Cyclopentane	287-92-3	0 - 2
Naphthalene	91-20-3	0 - 2
n-Nonane	111-84-2	0 - 2
Hydrogen sulfide	7783-06-4	< 1

**Composition comments**

Small amount of hydrogen sulfide, a highly toxic gas, may be present, especially in the headspace of containers.

**4. First-aid measures****Inhalation**

Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.

**Skin contact**

Remove contaminated clothing and shoes. Wash off immediately with soap and plenty of water. Get medical attention if irritation develops or persists. Wash clothing separately before reuse. Destroy or thoroughly clean contaminated shoes. If high pressure injection under the skin occurs, always seek medical attention.

**Eye contact**

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention.

**Ingestion**

Rinse mouth thoroughly. Do not induce vomiting without advice from poison control center. Do not give mouth-to-mouth resuscitation. If vomiting occurs, keep head low so that stomach content does not get into the lungs. Never give anything by mouth to a victim who is unconscious or is having convulsions. Get medical attention immediately.

<b>Most important symptoms/effects, acute and delayed</b>	Irritation of nose and throat. Irritation of eyes and mucous membranes. Skin irritation. Unconsciousness. Corneal damage. Narcosis. Cyanosis (blue tissue condition, nails, lips, and/or skin). Decrease in motor functions. Behavioral changes. Edema. Liver enlargement. Jaundice. Conjunctivitis. Proteinuria. Rash. Defatting of the skin.
<b>Indication of immediate medical attention and special treatment needed</b>	In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	If exposed or concerned: get medical attention/advice. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use.

## 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water spray. Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
<b>Unsuitable extinguishing media</b>	Do not use a solid water stream as it may scatter and spread fire.
<b>Specific hazards arising from the chemical</b>	Vapors can flow along surfaces to distant ignition source and flash back. Sensitive to static discharge. Vapors may cause a flash fire or ignite explosively.
<b>Special protective equipment and precautions for firefighters</b>	Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.
<b>Fire-fighting equipment/instructions</b>	Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Withdraw immediately in case of rising sound from venting safety devices or any discoloration of tanks due to fire. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Move containers from fire area if you can do it without risk. In the event of fire, cool tanks with water spray. Cool containers exposed to flames with water until well after the fire is out. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn. Vapors may form explosive air mixtures even at room temperature. Prevent buildup of vapors or gases to explosive concentrations. Some of these materials, if spilled, may evaporate leaving a flammable residue. Water runoff can cause environmental damage. Use compatible foam to minimize vapor generation as needed.
<b>Specific methods</b>	Use water spray to cool unopened containers.

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Local authorities should be advised if significant spills cannot be contained. Keep upwind. Keep out of low areas. Ventilate closed spaces before entering. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. See Section 8 of the SDS for Personal Protective Equipment.
<b>Methods and materials for containment and cleaning up</b>	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if possible without any risk. This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water. Dike the spilled material, where this is possible. Prevent entry into waterways, sewers, basements or confined areas. Use non-sparking tools and explosion-proof equipment.  Small Spills: Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Clean surface thoroughly to remove residual contamination. This material and its container must be disposed of as hazardous waste.  Large Spills: Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent product from entering drains. Do not allow material to contaminate ground water system. Should not be released into the environment. Clean up in accordance with all applicable regulations.

## Environmental precautions

Gasoline may contain oxygenated blend products (Ethanol, etc.) that are soluble in water and therefore precautions should be taken to protect surface and groundwater sources from contamination. If facility or operation has an "oil or hazardous substance contingency plan", activate its procedures. Stay upwind and away from spill. Wear appropriate protective equipment including respiratory protection as conditions warrant. Do not enter or stay in area unless monitoring indicates that it is safe to do so. Isolate hazard area and restrict entry to emergency crew. Extremely flammable. Review Firefighting Measures, Section 5, before proceeding with clean up. Keep all sources of ignition (flames, smoking, flares, etc.) and hot surfaces away from release. Contain spill in smallest possible area. Recover as much product as possible (e.g. by vacuuming). Stop leak if it can be done without risk. Use water spray to disperse vapors. Use compatible foam to minimize vapor generation as needed. Spilled material may be absorbed by an appropriate absorbent, and then handled in accordance with environmental regulations. Prevent spilled material from entering sewers, storm drains, other unauthorized treatment or drainage systems and natural waterways. Contact fire authorities and appropriate federal, state and local agencies. If spill of any amount is made into or upon navigable waters, the contiguous zone, or adjoining shorelines, contact the National Response Center at 1-800-424-8802.

## 7. Handling and storage

### Precautions for safe handling

Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Do not taste or swallow. Avoid prolonged exposure. Use only with adequate ventilation. Wash thoroughly after handling. The product is extremely flammable, and explosive vapor/air mixtures may be formed even at normal room temperatures. DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. When using, do not eat, drink or smoke. Avoid release to the environment.

### Conditions for safe storage, including any incompatibilities

Flammable liquid storage. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. The pressure in sealed containers can increase under the influence of heat. Keep container tightly closed in a cool, well-ventilated place. Keep away from food, drink and animal feedingstuffs. Keep out of the reach of children.

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Components	Type	Value
Benzene (CAS 71-43-2)	STEL	5 ppm
	TWA	1 ppm

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Cumene (CAS 98-82-8)	PEL	245 mg/m3 50 ppm
Cyclohexane (CAS 110-82-7)	PEL	1050 mg/m3 300 ppm
Ethylbenzene (CAS 100-41-4)	PEL	435 mg/m3 100 ppm
Naphthalene (CAS 91-20-3)	PEL	50 mg/m3 10 ppm
n-Heptane (CAS 142-82-5)	PEL	2000 mg/m3 500 ppm
n-Hexane (CAS 110-54-3)	PEL	1800 mg/m3 500 ppm
Pentane (CAS 109-66-0)	PEL	2950 mg/m3 1000 ppm
Xylene (o, m, p isomers) (CAS 1330-20-7)	PEL	435 mg/m3 100 ppm

**US. OSHA Table Z-2 (29 CFR 1910.1000)**

Components	Type	Value
Benzene (CAS 71-43-2)	Ceiling	25 ppm
	TWA	10 ppm
Hydrogen sulfide (CAS 7783-06-4)	Ceiling	20 ppm
Toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

**US. ACGIH Threshold Limit Values**

Components	Type	Value
1,2,4-Trimethylbenzene (CAS 95-63-6)	TWA	25 ppm
Benzene (CAS 71-43-2)	STEL	2.5 ppm
	TWA	0.5 ppm
Butylene (CAS 25167-67-3)	TWA	250 ppm
Cumene (CAS 98-82-8)	TWA	50 ppm
Cyclohexane (CAS 110-82-7)	TWA	100 ppm
Cyclopentane (CAS 287-92-3)	TWA	600 ppm
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm
Hexane (Other Isomers) (CAS 96-14-0)	STEL	1000 ppm
	TWA	500 ppm
Hydrogen sulfide (CAS 7783-06-4)	STEL	5 ppm
	TWA	1 ppm
Naphthalene (CAS 91-20-3)	STEL	15 ppm
	TWA	10 ppm
n-Heptane (CAS 142-82-5)	STEL	500 ppm
	TWA	400 ppm
n-Hexane (CAS 110-54-3)	TWA	50 ppm
n-Nonane (CAS 111-84-2)	TWA	200 ppm
Pentane (CAS 109-66-0)	TWA	600 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm
Xylene (o, m, p isomers) (CAS 1330-20-7)	STEL	150 ppm
	TWA	100 ppm

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value
1,2,4-Trimethylbenzene (CAS 95-63-6)	TWA	125 mg/m3
		25 ppm
Benzene (CAS 71-43-2)	STEL	1 ppm
	TWA	0.1 ppm
Cumene (CAS 98-82-8)	TWA	245 mg/m3
		50 ppm
Cyclohexane (CAS 110-82-7)	TWA	1050 mg/m3
		300 ppm
Cyclopentane (CAS 287-92-3)	TWA	1720 mg/m3
		600 ppm
Ethylbenzene (CAS 100-41-4)	STEL	545 mg/m3
		125 ppm

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value
	TWA	435 mg/m3
		100 ppm
Hexane (Other Isomers) (CAS 96-14-0)	Ceiling	1800 mg/m3
		510 ppm
	TWA	350 mg/m3
		100 ppm
Hydrogen sulfide (CAS 7783-06-4)	Ceiling	15 mg/m3
		10 ppm
Naphthalene (CAS 91-20-3)	STEL	75 mg/m3
		15 ppm
	TWA	50 mg/m3
		10 ppm
n-Heptane (CAS 142-82-5)	Ceiling	1800 mg/m3
		440 ppm
	TWA	350 mg/m3
		85 ppm
n-Hexane (CAS 110-54-3)	TWA	180 mg/m3
		50 ppm
n-Nonane (CAS 111-84-2)	TWA	1050 mg/m3
		200 ppm
Pentane (CAS 109-66-0)	Ceiling	1800 mg/m3
		610 ppm
	TWA	350 mg/m3
		120 ppm
Toluene (CAS 108-88-3)	STEL	560 mg/m3
		150 ppm
	TWA	375 mg/m3
		100 ppm
Xylene (o, m, p isomers) (CAS 1330-20-7)	STEL	655 mg/m3
		150 ppm
	TWA	435 mg/m3
		100 ppm

**Biological limit values**

**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Benzene (CAS 71-43-2)	25 µg/g	S-Phenylmercapturic acid	Creatinine in urine	*
Ethylbenzene (CAS 100-41-4)	0.7 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
n-Hexane (CAS 110-54-3)	0.4 mg/l	2,5-Hexanedione, without hydrolysis	Urine	*
	0.4 mg/l	2,5-Hexanedione, without hydrolysis		*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*
Xylene (o, m, p isomers) (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

\* - For sampling details, please see the source document.

## Exposure guidelines

### US - California OELs: Skin designation

Benzene (CAS 71-43-2)

Can be absorbed through the skin.

Cumene (CAS 98-82-8)

Can be absorbed through the skin.

n-Hexane (CAS 110-54-3)

Can be absorbed through the skin.

Toluene (CAS 108-88-3)

Can be absorbed through the skin.

### US - Minnesota Haz Subs: Skin designation applies

Cumene (CAS 98-82-8)

Skin designation applies.

Toluene (CAS 108-88-3)

Skin designation applies.

### US - Tennessee OELs: Skin designation

Cumene (CAS 98-82-8)

Can be absorbed through the skin.

### US ACGIH Threshold Limit Values: Skin designation

Benzene (CAS 71-43-2)

Can be absorbed through the skin.

Naphthalene (CAS 91-20-3)

Can be absorbed through the skin.

n-Hexane (CAS 110-54-3)

Can be absorbed through the skin.

### US. NIOSH: Pocket Guide to Chemical Hazards

Cumene (CAS 98-82-8)

Can be absorbed through the skin.

### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Cumene (CAS 98-82-8)

Can be absorbed through the skin.

### Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment.

### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Wear safety glasses. If splash potential exists, wear full face shield or chemical goggles.

#### Skin protection

##### Hand protection

Avoid exposure - obtain special instructions before use. Wear protective gloves. Protective gloves.

##### Other

Wear chemical-resistant, impervious gloves. Full body suit and boots are recommended when handling large volumes or in emergency situations. Flame retardant protective clothing is recommended.

#### Respiratory protection

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workplace exposure limits for product or components are exceeded, NIOSH approved equipment should be worn. Proper respirator selection should be determined by adequately trained personnel, based on the contaminants, the degree of potential exposure and published respiratory protection factors. This equipment should be available for nonroutine and emergency use.

#### Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

### General hygiene considerations

Avoid contact with eyes. Avoid contact with skin. Keep away from food and drink. Wash hands before breaks and immediately after handling the product. Provide eyewash station and safety shower. Handle in accordance with good industrial hygiene and safety practice.

## 9. Physical and chemical properties

### Appearance

Light straw to red clear liquid.

#### Physical state

Liquid.

#### Form

Liquid.

#### Color

Light straw to red clear.

### Odor

Characteristic Gasoline Odor (Strong).

### Odor threshold

Not available.

### pH

Not available.

### Melting point/freezing point

44 °F (6.67 °C) Estimated

### Initial boiling point and boiling range

> 97 °F (> 36.11 °C) Estimated

### Flash point

> -58.3 °F (> -50.2 °C) Closed Cup Estimated

### Evaporation rate

< 10.6 Estimated

### Flammability (solid, gas)

Not available.

## Upper/lower flammability or explosive limits

Flammability limit - lower (%) 1 %

Flammability limit - upper (%) 7 %

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density < 4.4 Estimated

Relative density 0.77 (Water=1) (60°F)

## Solubility(ies)

Solubility (water) Very slightly soluble.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature > 550 °F (> 287.78 °C)

Decomposition temperature Not available.

Viscosity Not available.

## Other information

Percent volatile Essentially 100%

## 10. Stability and reactivity

Reactivity Not available.

Chemical stability Stable under normal temperature conditions and recommended use.

Possibility of hazardous reactions Hazardous polymerization does not occur.

Conditions to avoid Heat, flames and sparks. Ignition sources. Contact with incompatible materials. Do not pressurize, cut, weld, braze, solder, drill, grind or expose empty containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode and cause injury or death.

Incompatible materials Strong oxidizing agents. Reducing agents. Acids. Alkalis.

Hazardous decomposition products No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

Ingestion May be fatal if swallowed and enters airways.

Inhalation Harmful if inhaled. In high concentrations, vapors and spray mists are narcotic and may cause headache, fatigue, dizziness and nausea.

Skin contact Causes skin irritation. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Eye contact May cause eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics Irritation of nose and throat. Irritation of eyes and mucous membranes. Skin irritation. Unconsciousness. Corneal damage. Narcosis. Cyanosis (blue tissue condition, nails, lips, and/or skin). Decrease in motor functions. Behavioral changes. Edema. Liver enlargement. Jaundice. Conjunctivitis. Proteinuria. Defatting of the skin. Rash.

### Information on toxicological effects

Acute toxicity Harmful if inhaled. Harmful: may cause lung damage if swallowed.

Components	Species	Test Results
1,2,4-Trimethylbenzene (CAS 95-63-6)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 3160 mg/kg
<i>Inhalation</i>		
LC50	Rat	18000 mg/m3, 4 hours



Components	Species	Test Results
Oral LD50	Rat	6 g/kg
Benzene (CAS 71-43-2)		
<b>Acute</b>		
Oral LD50	Rat	930 mg/kg
Cumene (CAS 98-82-8)		
<b>Acute</b>		
Inhalation LC50	Rat	8000 mg/l, 4 Hours
Oral LD50	Rat	1400 mg/kg
Cyclohexane (CAS 110-82-7)		
<b>Acute</b>		
Oral LD50	Rat	12705 mg/kg
Ethylbenzene (CAS 100-41-4)		
<b>Acute</b>		
Dermal LD50	Rabbit	> 5000 mg/kg
Oral LD50	Rat	5.46 g/kg
Hydrogen sulfide (CAS 7783-06-4)		
<b>Acute</b>		
Inhalation LC50	Rat	> 0.38 mg/l, 960 Minutes
Naphthalene (CAS 91-20-3)		
<b>Acute</b>		
Dermal LD50	Rabbit	> 2 g/kg
Oral LD50	Rat	490 mg/kg
n-Heptane (CAS 142-82-5)		
<b>Acute</b>		
Inhalation LC50	Rat	103 mg/l, 4 Hours
n-Hexane (CAS 110-54-3)		
<b>Acute</b>		
Oral LD50	Rat	28710 mg/kg
n-Nonane (CAS 111-84-2)		
<b>Acute</b>		
Inhalation LC50	Rat	3200 mg/l, 4 Hours
Pentane (CAS 109-66-0)		
<b>Acute</b>		
Inhalation LC50	Rat	364 mg/l, 4 Hours

Components	Species	Test Results
Toluene (CAS 108-88-3)		
<b>Acute</b>		
<i>Inhalation</i>		
LC50	Rat	8000 mg/l, 4 Hours
<i>Oral</i>		
LD50	Rat	2.6 g/kg
Xylene (o, m, p isomers) (CAS 1330-20-7)		
<b>Acute</b>		
<i>Oral</i>		
LD50	Rat	4300 mg/kg
<b>Skin corrosion/irritation</b>	Causes skin irritation.	
<b>Serious eye damage/eye irritation</b>	Based on available data, the classification criteria are not met.	
<b>Respiratory or skin sensitization</b>		
<b>Respiratory sensitization</b>	Based on available data, the classification criteria are not met.	
<b>Skin sensitization</b>	Based on available data, the classification criteria are not met.	
<b>Germ cell mutagenicity</b>	May cause genetic defects. In in-vitro experiments, neither benzene, toluene nor xylene changed the number of sister-chromatid exchanges (SCEs) or the number of chromosomal aberrations in human lymphocytes. However, toluene and xylene caused a significant cell growth inhibition which was not observed with benzene in the same concentrations. In in-vivo experiments, toluene changed the number of sister-chromatid exchanges (SCEs) in human lymphocytes. Toluene may cause heritable genetic damage.	
<b>Carcinogenicity</b>	May cause cancer.	
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>		
Benzene (CAS 71-43-2)	1 Carcinogenic to humans.	
Cumene (CAS 98-82-8)	2B Possibly carcinogenic to humans.	
Ethylbenzene (CAS 100-41-4)	2B Possibly carcinogenic to humans.	
Naphthalene (CAS 91-20-3)	2B Possibly carcinogenic to humans.	
Toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.	
Xylene (o, m, p isomers) (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.	
<b>NTP Report on Carcinogens</b>		
Benzene (CAS 71-43-2)	Known To Be Human Carcinogen.	
Naphthalene (CAS 91-20-3)	Reasonably Anticipated to be a Human Carcinogen.	
<b>US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)</b>		
Benzene (CAS 71-43-2)	Cancer	
<b>Reproductive toxicity</b>	Suspected of damaging fertility or the unborn child. Benzene, xylene and toluene have demonstrated animal effects of reproductive toxicity. Animal studies of benzene have shown testicular effects, alterations in reproductive cycles, chromosomal aberrations and embryo/fetotoxicity. May damage fertility or the unborn child. Can cause adverse reproductive effects - such as birth defects, miscarriages, or infertility. Avoid exposure to women during early pregnancy. Avoid contact during pregnancy/while nursing.	
<b>Specific target organ toxicity - single exposure</b>	May cause drowsiness or dizziness.	
<b>Specific target organ toxicity - repeated exposure</b>	May cause damage to the following organs through prolonged or repeated exposure: Blood. Liver. Kidney.	
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.	
<b>Chronic effects</b>	Prolonged and repeated exposure to benzene may cause serious injury to blood forming organs and is associated with anemia and to the later development of acute myelogenous leukemia (AML). Danger of serious damage to health by prolonged exposure. Prolonged or repeated overexposure may cause central nervous system, kidney, liver, and lung damage.	
<b>Further information</b>	Symptoms may be delayed.	

## 12. Ecological information

**Ecotoxicity** Toxic to aquatic life with long lasting effects.

Components		Species	Test Results
1,2,4-Trimethylbenzene (CAS 95-63-6)			
<b>Aquatic</b>			
Fish	LC50	Fathead minnow ( <i>Pimephales promelas</i> )	7.19 - 8.28 mg/l, 96 hours
Benzene (CAS 71-43-2)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea ( <i>Daphnia magna</i> )	8.76 - 15.6 mg/l, 48 Hours
Fish	LC50	Rainbow trout,donaldson trout ( <i>Oncorhynchus mykiss</i> )	5.9 mg/l, 96 hours
Cumene (CAS 98-82-8)			
<b>Aquatic</b>			
Crustacea	EC50	Brine shrimp ( <i>Artemia sp.</i> )	3.55 - 11.29 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout ( <i>Oncorhynchus mykiss</i> )	2.7 mg/l, 96 hours
Cyclohexane (CAS 110-82-7)			
<b>Aquatic</b>			
Fish	LC50	Fathead minnow ( <i>Pimephales promelas</i> )	3.961 - 5.181 mg/l, 96 hours
		Striped bass ( <i>Morone saxatilis</i> )	8.3 mg/l, 96 hours
Cyclopentane (CAS 287-92-3)			
<b>Aquatic</b>			
<i>Acute</i>			
Crustacea	EC50	<i>Daphnia magna</i>	10.5 mg/l, 48 hours
Ethylbenzene (CAS 100-41-4)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea ( <i>Daphnia magna</i> )	1 - 4 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout ( <i>Oncorhynchus mykiss</i> )	4 mg/l, 96 hours
Hydrogen sulfide (CAS 7783-06-4)			
<b>Aquatic</b>			
Fish	LC50	Lake whitefish ( <i>Coregonus clupeaformis</i> )	0.002 mg/l, 96 hours
Naphthalene (CAS 91-20-3)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea ( <i>Daphnia magna</i> )	1.09 - 3.4 mg/l, 48 hours
Fish	LC50	Pink salmon ( <i>Oncorhynchus gorbuscha</i> )	0.95 - 1.62 mg/l, 96 hours
n-Heptane (CAS 142-82-5)			
<b>Aquatic</b>			
Fish	LC50	Western mosquitofish ( <i>Gambusia affinis</i> )	4924 mg/l, 96 hours
n-Hexane (CAS 110-54-3)			
<b>Aquatic</b>			
Fish	LC50	Fathead minnow ( <i>Pimephales promelas</i> )	2.101 - 2.981 mg/l, 96 hours
Pentane (CAS 109-66-0)			
<b>Aquatic</b>			
Crustacea	EC50	<i>Daphnia</i>	2.3 mg/l, 48 Hours
Fish	LC50	Fish	3.1 mg/l, 96 Hours
Toluene (CAS 108-88-3)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea ( <i>Daphnia magna</i> )	5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Pink salmon ( <i>Oncorhynchus gorbuscha</i> )	7.45 - 8.78 mg/l, 96 hours

Components	Species	Test Results
Xylene (o, m, p isomers) (CAS 1330-20-7)		
<b>Aquatic</b>		
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)
		8 mg/l, 96 Hours
<b>Persistence and degradability</b>	None known.	
<b>Bioaccumulative potential</b>	Not available.	
<b>Partition coefficient n-octanol / water (log Kow)</b>		
Benzene (CAS 71-43-2)		2.13
Cumene (CAS 98-82-8)		3.66
Cyclohexane (CAS 110-82-7)		3.44
Cyclopentane (CAS 287-92-3)		3
Ethylbenzene (CAS 100-41-4)		3.15
Hexane (Other Isomers) (CAS 96-14-0)		3.6
Pentane (CAS 109-66-0)		3.39
Toluene (CAS 108-88-3)		2.73
Xylene (o, m, p isomers) (CAS 1330-20-7)		3.2
n-Heptane (CAS 142-82-5)		4.66
n-Hexane (CAS 110-54-3)		3.9
n-Nonane (CAS 111-84-2)		5.46
<b>Mobility in soil</b>	Not available.	
<b>Other adverse effects</b>	Not available.	
<b>13. Disposal considerations</b>		
<b>Disposal instructions</b>	Dispose in accordance with all applicable regulations. This material and its container must be disposed of as hazardous waste. Dispose of this material and its container to hazardous or special waste collection point. Incinerate the material under controlled conditions in an approved incinerator. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container.	
<b>Hazardous waste code</b>	D001: Waste Flammable material with a flash point <140 °F D018: Waste Benzene	
<b>US RCRA Hazardous Waste U List: Reference</b>		
Benzene (CAS 71-43-2)		U019
Cumene (CAS 98-82-8)		U055
Cyclohexane (CAS 110-82-7)		U056
Hydrogen sulfide (CAS 7783-06-4)		U135
Naphthalene (CAS 91-20-3)		U165
Toluene (CAS 108-88-3)		U220
Xylene (o, m, p isomers) (CAS 1330-20-7)		U239
<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations.	
<b>Contaminated packaging</b>	Offer rinsed packaging material to local recycling facilities.	
<b>14. Transport information</b>		
<b>DOT</b>		
<b>UN number</b>	UN1268	
<b>UN proper shipping name</b>	Petroleum distillates n.o.s.	
<b>Transport hazard class(es)</b>		
<b>Class</b>	3	
<b>Subsidiary risk</b>	-	
<b>Packing group</b>	I	
<b>Environmental hazards</b>		
<b>Marine pollutant</b>	Yes	
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.	
<b>Special provisions</b>	144, T11, TP1, TP8	
<b>Packaging exceptions</b>	150	
<b>Packaging non bulk</b>	201	
<b>Packaging bulk</b>	243	
<b>IATA</b>		
<b>UN number</b>	UN1268	

**UN proper shipping name** Petroleum distillates, n.o.s.  
**Transport hazard class(es)**  
**Class** 3  
**Subsidiary risk** -  
**Label(s)** 3  
**Packing group** I  
**Environmental hazards** Yes  
**ERG Code** 3H  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

#### IMDG

**UN number** UN1268  
**UN proper shipping name** PETROLEUM DISTILLATES, N.O.S.  
**Transport hazard class(es)**  
**Class** 3  
**Subsidiary risk** -  
**Label(s)** 3  
**Packing group** I  
**Environmental hazards**  
**Marine pollutant** Yes  
**EmS** F-E, S-E  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.  
**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable. However, this product is a liquid and if transported in bulk covered under MARPOL 73/78, Annex I.

## 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.  
 All components are on the U.S. EPA TSCA Inventory List.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

n-Nonane (CAS 111-84-2) 1.0 % One-Time Export Notification only.

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Benzene (CAS 71-43-2) Cancer  
 Central nervous system  
 Blood  
 Aspiration  
 Skin  
 Eye  
 Respiratory tract irritation  
 Flammability

#### CERCLA Hazardous Substance List (40 CFR 302.4)

Benzene (CAS 71-43-2)	LISTED
Cumene (CAS 98-82-8)	LISTED
Cyclohexane (CAS 110-82-7)	LISTED
Cyclopentane (CAS 287-92-3)	LISTED
Ethylbenzene (CAS 100-41-4)	LISTED
Hexane (Other Isomers) (CAS 96-14-0)	LISTED
Hydrogen sulfide (CAS 7783-06-4)	LISTED
Naphthalene (CAS 91-20-3)	LISTED
n-Heptane (CAS 142-82-5)	LISTED
n-Hexane (CAS 110-54-3)	LISTED
n-Nonane (CAS 111-84-2)	LISTED
Pentane (CAS 109-66-0)	LISTED
Toluene (CAS 108-88-3)	LISTED
Xylene (o, m, p isomers) (CAS 1330-20-7)	LISTED

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories** Immediate Hazard - No  
 Delayed Hazard - No  
 Fire Hazard - No  
 Pressure Hazard - No  
 Reactivity Hazard - No

**SARA 302 Extremely hazardous substance**

Chemical name	CAS number	Reportable quantity	Threshold planning quantity	Threshold planning quantity, lower value	Threshold planning quantity, upper value
Hydrogen sulfide	7783-06-4	100	500 lbs		

**SARA 311/312 Hazardous chemical** Yes

**SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
Toluene	108-88-3	0 - 10
Xylene (o, m, p isomers)	1330-20-7	0 - 10
1,2,4-Trimethylbenzene	95-63-6	0 - 5
Benzene	71-43-2	0 - 5
Cumene	98-82-8	0 - 5
Cyclohexane	110-82-7	0 - 5
Ethylbenzene	100-41-4	0 - 5
n-Hexane	110-54-3	0 - 3
Naphthalene	91-20-3	0 - 2

**Other federal regulations****Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Benzene (CAS 71-43-2)  
 Cumene (CAS 98-82-8)  
 Ethylbenzene (CAS 100-41-4)  
 Naphthalene (CAS 91-20-3)  
 n-Hexane (CAS 110-54-3)  
 Toluene (CAS 108-88-3)  
 Xylene (o, m, p isomers) (CAS 1330-20-7)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Hydrogen sulfide (CAS 7783-06-4)  
 Pentane (CAS 109-66-0)

**Safe Drinking Water Act (SDWA)** Not regulated.

**Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number**

Toluene (CAS 108-88-3) 6594

**Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))**

Toluene (CAS 108-88-3) 35 % weight/volumn

**DEA Exempt Chemical Mixtures Code Number**

Toluene (CAS 108-88-3) 594

**US state regulations** WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

**US. Massachusetts RTK - Substance List**

1,2,4-Trimethylbenzene (CAS 95-63-6)  
 Benzene (CAS 71-43-2)  
 Cumene (CAS 98-82-8)  
 Cyclohexane (CAS 110-82-7)  
 Cyclopentane (CAS 287-92-3)  
 Ethylbenzene (CAS 100-41-4)  
 Hexane (Other Isomers) (CAS 96-14-0)  
 Hydrogen sulfide (CAS 7783-06-4)  
 Naphthalene (CAS 91-20-3)  
 n-Heptane (CAS 142-82-5)  
 n-Hexane (CAS 110-54-3)  
 n-Nonane (CAS 111-84-2)  
 Pentane (CAS 109-66-0)

Toluene (CAS 108-88-3)  
Xylene (o, m, p isomers) (CAS 1330-20-7)

**US. New Jersey Worker and Community Right-to-Know Act**

1,2,4-Trimethylbenzene (CAS 95-63-6)  
Benzene (CAS 71-43-2)  
Cumene (CAS 98-82-8)  
Cyclohexane (CAS 110-82-7)  
Cyclopentane (CAS 287-92-3)  
Ethylbenzene (CAS 100-41-4)  
Hydrogen sulfide (CAS 7783-06-4)  
Naphthalene (CAS 91-20-3)  
n-Heptane (CAS 142-82-5)  
n-Hexane (CAS 110-54-3)  
n-Nonane (CAS 111-84-2)  
Pentane (CAS 109-66-0)  
Toluene (CAS 108-88-3)  
Xylene (o, m, p isomers) (CAS 1330-20-7)

**US. Pennsylvania Worker and Community Right-to-Know Law**

1,2,4-Trimethylbenzene (CAS 95-63-6)  
Benzene (CAS 71-43-2)  
Cumene (CAS 98-82-8)  
Cyclohexane (CAS 110-82-7)  
Cyclopentane (CAS 287-92-3)  
Ethylbenzene (CAS 100-41-4)  
Hexane (Other Isomers) (CAS 96-14-0)  
Hydrogen sulfide (CAS 7783-06-4)  
Naphthalene (CAS 91-20-3)  
n-Heptane (CAS 142-82-5)  
n-Hexane (CAS 110-54-3)  
n-Nonane (CAS 111-84-2)  
Pentane (CAS 109-66-0)  
Toluene (CAS 108-88-3)  
Xylene (o, m, p isomers) (CAS 1330-20-7)

**US. Rhode Island RTK**

1,2,4-Trimethylbenzene (CAS 95-63-6)  
Benzene (CAS 71-43-2)  
Cumene (CAS 98-82-8)  
Cyclohexane (CAS 110-82-7)  
Ethylbenzene (CAS 100-41-4)  
Hydrogen sulfide (CAS 7783-06-4)  
Naphthalene (CAS 91-20-3)  
n-Hexane (CAS 110-54-3)  
Pentane (CAS 109-66-0)  
Toluene (CAS 108-88-3)  
Xylene (o, m, p isomers) (CAS 1330-20-7)

**US. California Proposition 65**

**US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance**

Benzene (CAS 71-43-2)  
Cumene (CAS 98-82-8)  
Ethylbenzene (CAS 100-41-4)  
Naphthalene (CAS 91-20-3)  
Toluene (CAS 108-88-3)

**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No

Country(s) or region	Inventory name	On inventory (yes/no)*
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).


## 16. Other information, including date of preparation or last revision

**Issue date** 27-June-2013

**Revision date** 23-May-2014

**Version #** 02

**NFPA Ratings**



**References**

ACGIH  
 EPA: AQUIRE database  
 NLM: Hazardous Substances Data Base  
 US. IARC Monographs on Occupational Exposures to Chemical Agents  
 HSDB® - Hazardous Substances Data Bank  
 IARC Monographs. Overall Evaluation of Carcinogenicity  
 National Toxicology Program (NTP) Report on Carcinogens  
 ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

**Disclaimer**

This material Safety Data Sheet (SDS) was prepared in accordance with 29 CFR 1910.1200 by Valero Marketing & Supply Co., ("VALERO"). VALERO does not assume any liability arising out of product use by others. The information, recommendations, and suggestions presented in this SDS are based upon test results and data believed to be reliable. The end user of the product has the responsibility for evaluating the adequacy of the data under the conditions of use, determining the safety, toxicity and suitability of the product under these conditions, and obtaining additional or clarifying information where uncertainty exists. No guarantee expressed or implied is made as to the effects of such use, the results to be obtained, or the safety and toxicity of the product in any specific application. Furthermore, the information herein is not represented as absolutely complete, since it is not practicable to provide all the scientific and study information in the format of this document, plus additional information may be necessary under exceptional conditions of use, or because of applicable laws or government regulations.